


## Technical Data Sheet ARYAFILM - A434



ARYAPET A434 is one side chemical coated Polyester film suitable for flexible packaging application, the pretreatment provides very good metal adhesion, ink & solvent less laminating adhesives. This film is suitable for retortable & metallizable applications.



Sr. No.	. Properties		Unit	Test Method	Target	Minimum	Maximum
	•		Ge	eneral	•	•	•
	Thickness		Micron	JBF Method	12.0	11.64	12.36
1			Gauge		48.00	46.56	49.44
2	Yield		M <sup>2</sup> /Kg	JBF Method	59.52	57.79	61.36
3	Density		gm/cc	ASTM D 1505	1.395		
4	Roll width		mm	JBF Method	`-0,+3		
			Mec	hanical			
1	Tensile Strength at break	MD/TD	Kg/cm <sup>2</sup>	ASTM D 882	2000	1800	2200
1		ויוטן דט	(Kpsi)		28.4	25.6	31.3
2	Elongation at break	MD	%	ASTM D 882	130	90	170
2		TD	70		120	80	160
3	Co-efficient of friction (One to Other side)	Static		ASTM D 1894	0.45	0.35	0.55
J		Dynamic			0.40	0.30	0.50
			Th	ermal			
1	Shrinkage @ 150 <sup>0</sup> C/30′	MD	%	ASTM D 1204	1.6	1.2	2.0
1		TD			0.4	0.0	0.8
2	Melting Point		°C	DSC	252	250	255
			O <sub>l</sub>	ptical			
1	Haze		%	ASTM D 1003	3.5	2.5	4.5
2	Transmittance		%	ASTM D 1003	88.0	85.0	91.0
			Surface tre	eatment level			
1	Chemical Coated Side		Dyne/cm	ASTM D 2578	48	46	50
2	Plain side		Dyne/cm	ASTM D 2578	44	42	46
			Ba	arrier			
1	W.V.T.R. (38°C & 90% RH)		gm/m²/day	ASTM F 1249	40	30	50
			gm/100in²/day		2.58	1.94	3.23
2	O.T.R. (23°C & 0%RH)		cc/m²/day	ASTM D 3985	100	80	120
			cc/100in²/day		6.45	5.16	7.74

MD = Machine Direction, TD = Transverse Direction

Storage & Handling: ARYA FILM need to be stocked in a closed warehouse & should not be exposed to direct sun light or light sources. Avoid extreme of humidity and heat. It is recommended to store below 40°C in dry places in original packing & shelf life of above product is One year from date of Invoice.

Food Contact: ARYA FILM complies with EU10/2011 and US FDA regulations, Specific document and MSDS are available on request.

**Disclaimer:** The information given above is to the best of our knowledge and experience. Some of the properties can be changed as a result of suppliers' efforts to improve upon the quality or production efficiency of the subject. The information is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. JBF BAHRAIN W.L.L makes no warranty, express or implied, as to the fitness of the product for any specific use or purpose. The above data is purely for readers' consideration, investigation and verification and should be read in conjunction with the conditions for sale or contract

Website:www.jbfbahrain.com
T.D.S No.: JBF/TDS/B-479
Email: filminfo@jbfbah.com.bh Issue-2 Revision No.: 0 1st June 2024