


Technical Data Sheet ARYAFILM - A403



ARYAFILM A403 is One side Chemical coated transparent polyester film, this film is suitable for PU resins/inks



Sr. No.	Properties		Unit	Test Method	Target	Minimum	Maximum
			(General			
	Thickness		Micron	JBF Method	50	49	51
1			Gauge		200	196	204
2	Yield		M ² /Kg	JBF Method	14.29	14.01	14.58
3	Density		gm/cc	ASTM D 1505	1.395		
4	Service Temp		°C	JBF Method	-70 to 150		
			Me	echanical			
1	Tensile Strength at break	MD/TD	Kg/cm ²	- ASTM D 882	1900	1700	2100
			(Kpsi)		27.0	24.2	29.9
2	Elongation at break	MD	%	ASTM D 882	140	100	180
		TD			130	90	170
3	Co-efficient of friction (One side to Other side)	Static		ASTM D 1894	0.40	0.30	0.50
		Dynamic			0.35	0.25	0.45
			T	hermal			
1	Shrinkage @ 150° C/30′	MD	%	ASTM D 1204	1.6	1.0	2.2
		TD			0.4	0.0	0.8
2	Melting Point		°C	DSC	252	250	255
				Optical			
1	Haze		%	ASTM D 1003	7.0	5.5	8.5
2	Transmittance		%	ASTM D 1003	88	85	91
			Surface t	treatment level			
1	Chemical Coated Side		Dyne/cm	ASTM D 2578	70	68	72

MD = Machine Direction, TD = Transverse Direction

Storage & Handling: ARYA FILM need to be stocked in a closed warehouse & should not be exposed to direct sun light or light sources. Avoid extreme of humidity and heat. It is recommended to store below 40°C in dry places in original packing

Disclaimer: The information given above is to the best of our knowledge and experience. Some of the properties can be changed as a result of suppliers' efforts to improve upon the quality or production efficiency of the subject. The information is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. JBF makes no warranty, express or implied, as to the fitness of the product for any specific use or purpose. The above data is purely for readers' consideration, investigation and verification and should be read in conjunction with the conditions for sale or contract

Website: www.jbfrak.com Email: filminfo@jbfrak.ae T.D.S No. Revision 05 JBF/TDS/1192 10-July-2017