J	83	P		hnical Dat ARYAFILM		AR	YAF	ILM
ARYAFILM AM434 is Metalized on Chemically Coat surface promoting very high bond strength of the Metal & other side plain polyester film. Film is suita for flexible packaging applications.					Metalized surface Chemical coated Surface PET core Layer Standard Surface			ed Surface r
Sr. No.		Propertie	S	Unit	Test Method	Target	Minimum	Maximum
				Gene				
1	Thickness			Micron	JBF Method	12.00	11.64	12.36
1				Gauge		48.00	46.56	49.44
2	Yield			M <sup>2</sup> /Kg	JBF Method	59.52	57.79	61.36
				Mecha	nical			
1	Tensile Strength at break		MD/TD	Kg/cm <sup>2</sup>	ASTM D 882	2100	1900	2300
				(Kpsi)		29.9	27.0	32.7
2	Elongation at break		MD	%	ASTM D 882	130	90	170
			TD	70	ASTH D 002	120	80	160
3	Co-efficient of friction One side to Other side		Static		ASTM D 1894	0.60	0.50	0.70
			Dynamic			0.55	0.45	0.65
4	Metal Bond	Strength		gm/25 mm	TP-105-92	800	700	900
				Therr	nal		-	
1	Shrinkage @ 150 <sup>0</sup> C/30'		MD	- %	ASTM D 1204	2.0	1.4	2.6
			TD			0.4	0.0	0.8
2	Melting Poin	t		°C	DSC	252	250	255
				Surface treat	ment level			
1	Standard Surface			Dynes/cm	ASTM D 2578	44	42	46
				Barri				
				/.T.R. (ASTM F 1249) m2/day (38°C 90%RH)		O.T.R. (ASTM D 3985) cc/m2/day (23°C 0 %RH)		
	``	Maximu		· · ·	,			,
Target	Minimum		Target	Minimum	Maximum	Target	Minimum	Maximum
2.2	2.0	2.4	0.9	0.7	1.1	1.0	0.8	1.2
2.5	2.3	2.7	0.7	0.5	0.9	0.8	0.6	1.0
2.8	2.6	3.0	0.5	0.3	0.7	0.6	0.4	0.8
3.0	2.8	3.2	0.3	0.1	0.5	0.4	0.2	0.6

MD = Machine Direction, TD = Transverse Direction

To convert from m2/day to 100 inch2/day devide the m2 result by 15.5 ,

Storage & Handling: ARYA FILM need to be stocked in a closed warehouse & should not be exposed to direct sun light or light sources. Avoid extreme of humidity and heat. It is recommended to store below 40°C in dry places in original packing.

Food Contact: ARYA FILM complies with EC and FDA regulations on packaging for indirect contact with foodstuffs. Specific document and MSDS are available on request.

**Disclaimer:** The information given above is to the best of our knowledge and experience. Some of the properties can be changed as a result of suppliers' efforts to improve upon the quality or production efficiency of the subject. The information is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. **JBF** makes no warranty, express or implied, as to the fitness of the product for any specific use or purpose. The above data is purely for readers' consideration, investigation and verification and should be read in conjunction with the conditions for sale or contract.

Website: www.jbfrak.com

Email: filminfo@jbfrak.ae

TDS No : JBF/TDS/M-196

Revision: 07 Date : 01-Jun-19