| | | | hnical Data Sheet ARYAFILM AM444 | | AR | YAF | ILM | |
|---------------------|--|----------------------------|---|---|----------------------|--|--|-------------|
| corona i chemica | treated poly ally coated ions, espec | yester film suitable fo | ainable Meta other side A or candy wra xcellent glos | Antistatic pping | | | Metalized sur Corona treate PET core Laye Antistatic Surf | d side r |
| Sr. No. | | Properties | S | Unit | Test Method | Target | Minimum | Maximum |
| | | | | Gene | ral | | | |
| 1 | Thickness | | | Micron | JBF Method | 18.00 | 17.64 | 18.36 |
| 1 | | | | Gauge | יי יוכנווטע יוכנווטע | 72.00 | 70.56 | 73.44 |
| 2 | Yield | | | M ² /Kg | JBF Method | 39.68 | 38.90 | 40.49 |
| | | | | Mecha | nical | | T | |
| 1 | Tensile Strength at | | MD/TD | Kg/cm ² | ASTM D 882 | 2200 | 2000 | 2400 |
| - | break | | | (Kpsi) | //01110-002 | 31.3 | 28.4 | 34.1 |
| 2 | Elongation at break | | MD | % ASTM | ASTM D 882 | 130 | 90 | 170 |
| 2 | | | TD | | ASTH D 002 | 120 | 80 | 160 |
| 3 | Co-efficient | of friction | Static | 0 | ASTM D 1894 | 0.60 | 0.50 | 0.70 |
| 5 | One side to Other side | | Dynamic | | ASTM D 1094 | 0.55 | 0.45 | 0.65 |
| | | | | Therr | nal | | | |
| 1 | Shrinkage @ 150 ⁰ C/30' | | MD | % ASTM D : | ASTM D 1204 | 30.0 | 25.0 | 35.0 |
| | Shirikage @ | | | 70 | ASTRI D 1201 | 35.0 | 30.0 | 40.0 |
| 2 | Melting Point | | ٥C | DSC | 252 | 250 | 255 | |
| | | | | Surface treat | ment level | | | |
| 1 | Antistatic Su | irface | | - | ASTM D 2578 | 52 | 50 | 54 |
| | Dette - LD | 14 | | Barri | | 0.7 | | |
| (| | | | V.T.R. (ASTM F 1249) m2/day (38°C 90%RH) | | O.T.R. (ASTM D 3985) cc/m2/day (23°C 0 %RH) | | |
| Target | Minimum | Maximu | Target | Minimum | Maximum | Target | Minimum | Maximum |
| 2.2 | 2.0 | 2.4 | 0.9 | 0.7 | 1.1 | 1.0 | 0.8 | 1.2 |
| 2.5 | 2.3 | 2.7 | 0.7 | 0.5 | 0.9 | 0.8 | 0.6 | 1.0 |
| 2.8 | 2.6 | 3.0 | 0.5 | 0.3 | 0.7 | 0.6 | 0.4 | 0.8 |
| 3.0 | 2.8 | 3.2 | 0.3 | 0.1 | 0.5 | 0.4 | 0.2 | 0.6 |
| | | Fransverse Directi | | 0.1 | 0.0 | | 0.2 | 0.0 |

MD = Machine Direction, TD = Transverse Direction

To convert from m2/day to 100 inch2/day devide the m2 result by 15.5 ,

Storage & Handling: ARYA FILM need to be stocked in a closed warehouse & should not be exposed to direct sun light or light sources. Avoid extreme of humidity and heat. It is recommended to store below 40°C in dry places in original packing.

Food Contact: ARYA FILM complies with EC and FDA regulations on packaging for indirect contact with foodstuffs. Specific document and MSDS are available on request.

Disclaimer: The information given above is to the best of our knowledge and experience. Some of the properties can be changed as a result of suppliers' efforts to improve upon the quality or production efficiency of the subject. The information is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. **JBF** makes no warranty, express or implied, as to the fitness of the product for any specific use or purpose. The above data is purely for readers' consideration, investigation and verification and should be read in conjunction with the conditions for sale or contract.

| Website: www.jbfrak.com | TDS No : JBF/TDS/M-205 | | | |
|---------------------------|------------------------|------------------|--|--|
| Email: filminfo@jbfrak.ae | Revision: 07 | Date : 01-Jun-19 | | |